

11-15-00

A

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
UTILITY PATENT APPLICATION TRANSMITTAL LETTER

Attorney Docket No.: CT00-020

Mailing Date: November 14, 2000

Express Mail: EL568747333US

To: Assistant Commissioner for Patents
Box Patent Application
Washington D.C., 20231

Dear Sir:

Transmitted herewith for filing under 37 C.F.R. 1.53(b) is a:

- ☒ New Nonprovisional Utility Patent Application; or
- ☐ Continuation; or ☐ Divisional; or ☐ Continuation-In-Part (CIP);
of prior US Application No. _____, filed on _____, having U.S.
Examiner _____, in Group Art Unit _____

Of: Chia-Yu Fu, Thomas A. Wetteroth, and Rong-Fong Huang

For: **LOW PROFILE INTEGRATED MODULE INTERCONNECTS AND METHOD OF FABRICATION**

- ☒ 4 sheets of drawings and 32 pages of specification and claims.
- ☒ Newly executed oath or declaration combined with Power of Attorney on 4 pages.
- ☐ Copy of oath or declaration from prior U.S. application serial no. _____
☐ The following named inventor(s) from the prior application are hereby deleted from this application in accordance with 37 C.F.R. 1.63(d)(2) and 1.33(b):

- ☐ Foreign priority to EPO patent application having serial number _____ and a filing date of _____ is hereby claimed under 35 USC 119.
- ☒ An Assignment Transmittal Letter and Assignment of the invention to Motorola, Inc.
- ☐ An Information Disclosure Statement (IDS), with PTO-1449, and _____ citation copies.
- ☒ Return Receipt Postcard.
- ☐ Preliminary Amendment.
- ☐ Please cancel pending claims _____.
- ☐ Incorporation by Reference (for Continuation/Division/CIP application). The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein. Since the present application is based on a prior US application, please amend the specification by adding the following sentence before the first sentence of the specification:

"The present application is based on prior US application No. _____, filed on _____, which is hereby incorporated by reference, and priority thereto for common subject matter is hereby claimed."

- ☐ Applicant hereby petitions pursuant to 37 C.F.R. §1.136(a) for a _____ month extension of time for response to the outstanding Official Action mailed _____. The period for response was previously set to elapse _____, and is accordingly hereby extended to _____, which is still within the six-month statutory period for response (35 U.S.C. § 133) which elapses _____. The reason for this petition is that a Division, Continuation, or CIP is being filed, and it is desired to maintain the present application in pending condition pursuant to 35 USC § 120 through at least the filing of the Division, Continuation, or CIP application. The required Extension Fee established by 37 C.F.R. § 1.17(a) pursuant to 35 U.S.C. § 41(a) (8) is:

11/14/00 1053 U.S. PTO

PTO 09/11/00 6986

EXTENSION	FEE
<input type="checkbox"/> First Month	\$110.00
<input type="checkbox"/> Second Month	\$390.00
<input type="checkbox"/> Third Month	\$890.00
<input type="checkbox"/> Fourth Month	\$1,390.00
<input type="checkbox"/> Fifth Month	\$1,890.00

- ☒ The filing fee is calculated as follows:

CLAIMS AS FILED, LESS ANY CANCELED BY AMENDMENT

FOR	NUMBER OF CLAIMS	NUMBER EXTRA	RATE	FEE
TOTAL CLAIMS	32 - 20 =	12	x \$18	= \$ 216.00
INDEPENDENT CLAIMS	6 - 3 =	3	x \$80	= \$ 240.00
MULTIPLE DEPENDENT CLAIMS			\$270	= \$ 0.00
BASIC FEE				= \$ 710.00
TOTAL FILING FEE				= \$ 1166.00

- ☒ Please charge Deposit Account No. 13-4771 in the amount of \$ 1166.00 for the Total Filing Fee, and the Extension Fee under 37 C.F.R. §1.136(a), if applicable.
- ☒ The Commissioner is hereby authorized to charge any additional fees which may be required now or in the future during the entire pendency of this application under 37 C.F.R. 1.16 or 37 C.F.R. 1.17, including any present or future time extension fees which may be required, or credit any overpayment to Deposit Account No. 13-4771.
- ☒ This sheet is submitted in duplicate.

This transmittal letter has 2 total pages.

14 Nov 00
DATE

William E. Koch 29,659
William E. Koch REG. NO.

Motorola, Inc.
Customer Number: 23330

Attorney of Record
Telephone No.: (480) 441-4281
Facsimile No.: (480) 441-5220

LOW PROFILE INTEGRATED MODULE INTERCONNECTS
AND METHOD OF FABRICATION

5 Field of the Invention

This invention relates to apparatus and method for interconnecting integrated modules.

10 More particularly, the present invention relates to apparatus and method for interconnecting integrated modules with low profile interconnects having improved reliability.

15 Background of the Invention

At the present time, many electronic circuits are integrated into small components or modules that are then mounted on larger carriers, such as printed circuit boards and the like. One of the major problems that arises in this process is the differences in thermal expansion between the material making up the integrated modules and the material making up the carriers. For example, a commonly employed material for integrated modules is ceramic. Ceramic integrated modules are generally mounted on some type of printed circuit board employing a hard plastic. The difference in thermal expansion in these materials produces a thermal expansion mismatch that can

seriously effect the interconnect reliability and/or the life of the product.

Generally, the integrated modules have electrical traces distributed around the lower surface. In the prior art, the electrical traces of the integrated modules are electrically and physically connected to mounting and connecting pads on a printed circuit board by means of solder balls. The center of the module's lower surface can be considered as a zero stress or neutral point with connections spaced from the center having more stress, and the farther connections are spaced from the center the more stress they realize. Some of this stress is relieved by the solder balls, which provide a small amount of resiliency or movement. To further relieve this stress, the height of the solder ball is increased. The standoff height and the distance of the solder joint from the thermal expansion neutral point are well known to be the most critical factors responsible for solder joint thermal fatigue. Higher standoff heights and smaller distances from the thermal expansion neutral point are preferable.

Present demands for lower profile structures and larger integrated modules pose serious reliability issues. Generally, a customer specifies a maximum height (the distance between the surface of the mounting board and the upper surface of the module) that can be tolerated. The manufacturer must then arrange a compromise between the standoff height and the amount and position of the components in the module. Clearly, as the standoff height

is increased to improve the interconnect thermal fatigue life, the number of components in the module must be reduced to achieve the specified maximum height.

Accordingly it would be highly desirable to provide
5 apparatus and a method of reducing the standoff height and improving solder joint thermal fatigue life without reducing the reliability.

10 Brief Description of the Drawings

Referring to the drawings:

FIG. 1 is a simplified side view of a prior art
module, illustrating the mounting structure;

15 FIG. 2 is a simplified view in bottom plan of a prior art module, illustrating thermal expansion distances from the thermal expansion neutral point;

FIG. 3 is an enlarged sectional view of a portion of
an assembly including a plurality of modules in accordance
20 with the present invention;

FIG. 4 is a greatly enlarged, detailed view of a
portion of a single layer of the assembly of FIG. 3;

FIG. 5 is a simplified side view of a single module
after being cut from adjacent modules in the assembly of
25 FIG. 3;

FIG. 6 is a simplified view in bottom plan of the
module of FIG. 5;

FIG. 7 is a view in bottom plan, similar to FIG. 6, of a module including a stress relief anchor pad;

FIG. 8 is an enlarged sectional view of a single solder connection to a module in accordance with the present invention, taken along line 8-8 of FIG. 7;

FIG. 9 is a top view of a portion of the module in accordance with FIG. 8;

FIG. 10 is an enlarged sectional view of another single solder connection to a module in accordance with the present invention; and

FIG. 11 is a top view of a portion of the module in accordance with FIG. 10.

Description of the Preferred Embodiments

Turning now to FIG. 1, a simplified side view of a prior art module 10 is illustrated. Module 10 includes a plurality of terminals 11 formed on the lower surface thereof. As is well known in the art, terminals 11 are connected internally to the circuits and components integrated within module 10. Terminals 11 also serve to mount module 10 on a supporting substrate 12. Supporting substrate 12 has a plurality of mounting/connecting pads 14 formed on the upper or mounting surface 15 and positioned to coincide with terminals 11 of module 10. Solder balls 16 are positioned between terminals 11 and mounting/connecting pads 14. During assembly, solder balls 16 are partially melted so as to physically and

electrically adhere to terminals 11 and mounting/connecting pads 14. Thus, solder balls 16 physically mount module 10 on supporting substrate 12 and electrically connect terminals 11 to mounting/connecting pads 14.

Referring additionally to FIG. 2, a central point, designated 17, of the lower surface of module 10 is considered as a zero stress or neutral point with terminals 11 spaced from point 17 having increasing amounts of stress. The farther terminals 11 are spaced from point 17 the more stress they realize. In the example illustrated in FIG. 2, a terminal 11 situated in the corner of module 10 is spaced the farthest from point 17 and experiences the most stress, indicated by an arrow 18. Some of this stress is relieved by solder balls 16 (see FIG. 1), which provide a small amount of resiliency or movement. To improve the stress relieving characteristics of solder balls 16, the standoff height (designated h_s in FIG. 1) between the lower surface of module 10 and upper surface 15 of supporting substrate 12 is increased. The standoff height h_s and the distance of the solder joint from thermal expansion neutral point 17 are well known to be the most critical factors responsible for SMT solder joint thermal fatigue.

Present demands from customers include fabricating products with lower profiles, designated h in FIG. 1. Also, integrated modules are becoming larger. Both the lower profiles and the larger modules pose serious

reliability issues since they directly conflict with higher standoff heights and shorter distances from neutral point 17. When a customer specifies a maximum height h that can be tolerated, the manufacturer must compromise between standoff height h_s and the amount and position of the components in the module. Clearly, as standoff height h_s is increased to improve the solder joint thermal fatigue life, the number of components that can be included in module 10 must be reduced to achieve the specified maximum height h .

Turning now to FIG. 3, an enlarged sectional view is illustrated of a portion of an assembly or stack 20 including a plurality of modules 21, 22, and 23. Assembly 20 is illustrated to aid in describing a method of fabricating a low profile integrated module, in accordance with the present invention. Here it should be specifically understood that assembly 20 could include a wide variety of sheets of materials, such as ceramic materials, high density interconnect printed circuit boards (HDI/PCB), presently known as FR4, and substantially any material wherein electrical circuits and components are included in sheets and stacked to form a complete circuit or electrical component.

In this preferred embodiment, a plurality of sheets 25 of unfired or green ceramic material are provided for exemplary purposes. A typical example of one sheet 25 is illustrated in FIG. 4. Each sheet 25 includes a plurality of module components 26 defined by sides 27 and formed

adjacent each other so as to share sides 27. Each component 26 includes some electrical traces (designated 28 in FIG. 4), and may further include some electrical components such as capacitors, inductors, resistors, semiconductor integrated circuits (such as an IC designated 29), etc. Each component 26 also includes vias extending therethrough, some of which (designated 30) are located intermediately between sides 27 and some of which (designated 32) are formed in an elongated configuration to extend across sides 27 into adjacent components 26.

In a preferred embodiment, vias 30 are formed, using punches, drills, lasers, etc. (hereinafter referred to as "punching"). Vias 32 are formed by punching a plurality of adjacent, partially overlapping, substantially round holes (referred to hereinafter as nibbling) to define a single via with an elongated cross-section. It will of course be understood that various sizes and shapes of vias can be formed, including but not limited to square, rectangular, round, oblong, etc., using, for example, nibbling and the round and elongated vias shown in FIGS. 4 and 6 are illustrated only to simplify an understanding of the fabrication process. As an example of the size of the various vias, the cross-sectional dimension of the exposed face of via 32, designated 33 in FIG. 6, is in a range of 125 μm to 500 μm .

As stated above, sheets 25 are formed of unfired or green ceramic material which, as is known in the art, usually includes Al_2O_3 particles, glass particles, and a

binder, generally including organic material. After all of the vias 30 and 32 are properly formed in sheet 25, a metal paste, in this preferred embodiment an 80% silver and a solvent, is forced into the vias as, for example, by using a squeegee or the like. The solvent in the silver paste has a tendency to creep into the unfired ceramic material sides of the vias and firmly bind the silver paste in the vias. Here it will be understood that the metal paste can include any electrically conductive metal with a melting point generally greater than the firing temperature of the green ceramic sheets, i.e., generally greater than 800°C. It will further be understood that normal solders and the like can be used, if desired, in sheets of material which do not require high temperature curing or firing, such as the FR4 mentioned above.

Turning again to FIG. 3, it can be seen that a plurality of sheets 25 (in this example three) are stacked or positioned in overlying relationship with sides 27 and vias 32 vertically aligned to form common vias 32 and common sides 27 through the entire stack. It will of course be understood that internal vias 30 and various other connections are also aligned to provide one or more complete interconnected circuits.

Another plurality of sheets 35, formed of unfired or green ceramic material similar to sheets 25, are fabricated to include module components similar to module components 26 of sheets 25. Generally, the fabrication process for sheets 35 is similar to that described above

for sheets 25, except that vias 32 are not included.

Sheets 35 include some electrical traces, and may also include some electrical components such as capacitors, inductors, resistors, semiconductor integrated circuits, etc. Further, Sheets 35 include intermediate vias, similar to vias 30 in sheets 25, to provide interconnects between the various sheets 35 and 25. The plurality of sheets 35 (in this example three) are stacked or positioned in overlying relationship with the sides and any vias and components aligned to form one or more complete interconnected circuits.

As can be seen from FIG. 3, sheets 25 are stacked in overlying relationship over sheets 35 with sides 27 aligned so as to form a plurality of vertically aligned modules 21, 22, and 23. Modules 21, 22, and 23 are positioned in adjacent abutting relationship so as to share common sides 27 with the next adjacent module on each side. As is understood by those skilled in the art, sheets 25 and 35 are very thin and, generally, the total number of sheets used depends upon the circuit or circuits being integrated as well as any limitations on the height h specified by a user of the module (e.g., 2 mm).

Further, the number of sheets 25 and the number of sheets 35 incorporated, depends upon a desired vertical length for the common vias 32. Practically, the number of sheets included in stack 20 could vary from a minimum of one sheet 25 and one sheet 35 to as many as twenty total sheets, or more. In this preferred embodiment, the number

of sheets 25 and the number of sheets 35 in stack 20 is determined so that the common vias 32 extend vertically in a range from approximately 25 μm to approximately one half of the height of the stack (i.e., a distance between a lower surface of a lower sheet and an upper surface of an upper sheet).

It should be understood that, while a specific procedure for assembling stack 20 of sheets 25 and sheets 35 has been described in a way that enhances the understanding, any convenient assembly procedure may be followed. For example, it is generally expedient to form all of the required sheets 25 and 35 in advance and then stack them in the aligned position in one step. The exact sequence of steps described above and hereafter in achieving the stack of sheets is not critical to the invention and may be varied according to specific embodiments being fabricated.

Once stack 20 of unfired or green ceramic sheets has been assembled as illustrated in FIG. 3, the stack is cut or otherwise divided into individual modules. In this preferred embodiment stack 20 is cut with a very sharp instrument. The cutting is easily accomplished since sheets 25 and 35 are still formed of unfired or green ceramic. Stack 20 could be divided into individual modules after firing but fired ceramic is very hard and the process would be substantially more difficult. In FIG. 3, the sides 27 of adjacent modules 21 and 23 and adjacent modules 21 and 22 are indicated with broken

lines. Here it should be noted that sides 27 extend through vias 32 so that upon cutting stack 20 along the broken lines each module 21, 22, and 23 has portions of vias 32 extending along the sides thereof, as illustrated in FIG. 6. Also, the cutting process is performed with sheets 25 at the top of the stack and sheets 35 at the bottom of the stack so that silver paste in vias 32 is held in place by the solid surface of sheets 35 during the cutting operation.

Once stack 20 is separated into individual modules (e.g. modules 21, 22, and 23), the modules are fired to cure the ceramic. As is understood in the art, the firing temperature is generally dictated by the composition of the green ceramic material. In this preferred embodiment, the green ceramic material includes Al_2O_3 particles, glass particles and an organic binder. In this case, the glass particles dictate the firing temperature, since the glass particles melt sufficiently to bind the aluminum particles together at a temperature of approximately 875°C . Also, at this temperature the organic binder is driven off to leave a ceramic comprising Al_2O_3 particles bound together by at the least partially melted and reformed glass. Also, the various sheets 25 and 35 are bound into a virtually single structure by the firing process. In the firing process the individual modules contract or shrink approximately 13%, but the shrinkage is substantially uniform so that it does not affect the final module.

Further, during the firing process the silver paste in vias 30 and 32 is hardened firmly into position.

Turning now to FIG. 7, a bottom view of another final module 21 is illustrated. A plurality of vias 32 are distributed along each side 27 and a stress relief anchor pad is positioned on the bottom surface. In this specific embodiment, the stress relief pad includes a centrally located octagonal element 36 and a round element 37 positioned in each corner. The stress relief pad is formed on the lower surface of the final sheet 25 (e.g., the top sheet in FIG. 3) and includes metal that is ultimately soldered to a supporting substrate (as will be described presently).

As explained briefly above, a central point of the lower surface of a module is considered as a zero stress or neutral point and the farther terminals are spaced from the neutral point the more stress they realize. In the embodiment illustrated in FIG. 7, the stress relief pad reduces stresses at adjacent interconnects or vias 32. Octagonal element 36 and round elements 37 are designed and positioned so that each via 32 is spaced approximately an equal and short distance therefrom. It will be understood that octagonal element 36 and round elements 37 could be formed as a single integrated stress relief pad if desired or they could be divided into additional elements, with the purpose being to provide equal and short distances between each via and the stress relief pad.

The individual fired modules (e.g., module 21) can then be mounted on a supporting substrate 40, as illustrated in FIG. 8. In this preferred embodiment, supporting substrate 40 is a printed circuit board or the like with a mounting surface 42. Mounting pads 43 are fabricated on surface 42 using any well known process and a layer of reflowable solder or solder paste is applied using any well known technique, such as printing or the like. While only one mounting pad 43 is illustrated in FIG. 8, for convenience, it will be understood that any or all of vias 32, any vias 30, and/or any stress relief pad or pads, which it is desired to connect to supporting substrate 40, will generally have an aligned mounting pad 43 associated therewith.

Referring additionally to FIG. 9, it can be seen that mounting pads 43 are formed with a surface area that is larger than the lower or adjoining surface area of the associated via 32. As an example, if via 32 is formed with a rectangular cross-sectional area having a maximum side dimension of approximately 125 μm , the surface area of mounting pad 43 may be generally rectangular with a length to width ratio of about 2:1. Solder (e.g., solder paste, etc.) is prepositioned on mounting pad 43, by solder printing or the like, to achieve a desired amount. The structure is then heated in a well known fashion to melt or reflow the solder paste or solder positioned on mounting pad 43. The prepositioned solder wicks-up the outside of via 32 to form a fillet 45, as illustrated in

FIG. 8. The amount of prepositioned solder is selected so that the final standoff height h_s is preferably in a range of from 75 μm to 125 μm . This range allows the solder associated with the module to be printed at the same time as solder for other board elements or modules and the entire board 40 can be printed in one step.

Referring again to FIGS. 8 and 9, a connection and/or mounting pad 46 is provided on the lower surface of the lower sheet 25 of module 21 in contact with the lower surface of each via 32. Pad 46 has a surface area larger than the cross-sectional area of via 32 (see FIG. 8) so as to spread the stress over a larger area. The surface area of mounting pad 43 on supporting substrate 40 is then formed with a generally rectangular shape having a length to width ratio of about 2:1 and a surface area at least twice as large as the surface area of pad 46 (see FIG. 9).

Turning to FIGS. 10 and 11, another embodiment of apparatus for reducing stress is illustrated. In this embodiment, components similar to those illustrated in FIGS. 8 and 9 are designated with similar numbers and a prime is added to each number to indicate the different embodiment. In this embodiment, a connection and/or mounting pad 46' is provided on the lower surface of an interior sheet next to the lower sheet, with one or more lower sheets 25' having cutouts aligned with pad 46'. While only one mounting pad 43' is illustrated in FIGS. 10 and 11, for convenience, it will be understood that any or all of vias 32', any vias 30', and/or any stress relief

pad or pads, which it is desired to connect to supporting substrate 40', will generally have an aligned mounting pad 43' associated therewith. In this embodiment, pad 46' is recessed into the lower surface of module 21' so that the total height of the solder, designated h_{s01} in FIG. 10, is greater and, therefore, further reduces the stress on the joint. Depending upon the specific application and the number of vias required, pad 46' can be recessed one to several sheets of module 21' to increase the height h_{s01} .

10 It should also be noted that by recessing pad 46', the standoff height h_s of module 21' can be reduced to 25 μ m or less if it is desired.

One additional problem that arises is the tendency of the silver to be scavenged or alloyed with any Sn based solder during the reflow (high temperature) process.

15 Because of this scavenging or alloying, the integrity of solder interconnects becomes brittle and weakened. The effects of the scavenging or alloying of the silver can be overcome by providing a larger quantity of silver. For example, pad 46' can be formed of silver in a fashion similar to that described for the filling of the vias. In some specific applications, the cutout or cutouts in the lower sheet or sheets 25' of module 21' can be filled with silver in a fashion similar to that described for the filling of the vias. This cutout enables a thickness increase from 47 to 47' which will provide the additional silver to ensure strong interconnections.

20

25

Thus, vias 32 positioned in sides 27 of module 21 are constructed to extend only partially up the sides so as to improve the fabrication process. By extending vias 32 only partially up sides 27, the internal circuitry can be easily connected through internal electrical traces 28 and vias 30. The assembled or stacked unfired ceramic sheets of integrated circuitry are separated or cut while in the green state to greatly simplify the separation process. Further, by extending vias 32 only partially up sides 27, sheets 35 form a base for the silver or conductive metal in vias 32 so that they can be easily bisected without driving the silver or conductive metal out.

The fired and otherwise completed integrated modules are mounted on a supporting substrate with a greatly reduced standoff height h_s' (e.g., 75 μm to 125 μm versus a 375 μm ball in the prior art). Because of the conductive metal filled vias positioned along the edge and the size of the mounting pads on the supporting substrate, the solder used in the mounting and connecting process wicks-up the side of the module to form a fillet, which greatly strengthens the connection/mount and substantially increases reliability and life of the solder joint.

While we have shown and described specific embodiments of the present invention, further modifications and improvements will occur to those skilled in the art. We desire it to be understood, therefore, that this invention is not limited to the particular forms shown and we intend in the appended claims to cover all

modifications that do not depart from the spirit and scope
of this invention.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
222

What is claimed is:

1. A method of fabricating a low profile integrated module comprising the steps of:

5 providing a first sheet of material defining two adjacent integrated module first components, and forming a via extending through the first sheet between the two adjacent integrated module first components;

filling the via with a conductive metal;

10 providing a second sheet of material defining two adjacent integrated module second components;

fixing the first and second sheets in overlying relationship with the two adjacent integrated module first components aligned with the two adjacent integrated module
15 second components to form two adjacent integrated modules; and

cutting the first and second sheets, through the via to separate the first and second sheets into separate integrated modules, each module having a portion of the
20 via filled with conductive metal in a periphery thereof and extending along a portion of the periphery.

2. A method of fabricating a low profile integrated module as claimed in claim 1 wherein the steps of

25 providing the first sheet of material and providing the second sheet of material include providing sheets of printed circuit boards.

3. A method of fabricating a low profile integrated module as claimed in claim 2 wherein the step of filling the via with the conductive metal includes filling the via with a solder paste.

5

4. A method of fabricating a low profile integrated module as claimed in claim 1 wherein the steps of providing the first sheet of material and providing the second sheet of material include providing sheets of unfired ceramic material.

10

5. A method of fabricating a low profile integrated module as claimed in claim 4 wherein the steps of providing sheets of unfired ceramic material include providing sheets of Al_2O_3 , glass particles and a binder.

15

6. A method of fabricating a low profile integrated module as claimed in claim 5 further including a step of firing the unfired ceramic material subsequent to the cutting step at a firing temperature high enough to form ceramic modules.

20

7. A method of fabricating a low profile integrated module as claimed in claim 6 wherein the step of filling the via with the conductive metal includes using a conductive metal with a melting temperature greater than the firing temperature.

25

8. A method of fabricating a low profile integrated module as claimed in claim 1 wherein the step of providing the first sheet of material further includes providing a plurality of first sheets of material each including a via
5 extending therethrough.

9. A method of fabricating a low profile integrated module as claimed in claim 8 wherein the step of providing the second sheet of material further includes providing a
10 plurality of second sheets of material.

10. A method of fabricating a low profile integrated module as claimed in claim 8 wherein the step of fixing the first and second sheets in overlying relationship
15 aligns vias in the plurality of first sheets to produce a common via extending partially through the two adjacent integrated modules from a lower surface of a lower sheet to an upper surface of an intermediate sheet.

20 11. A method of fabricating a low profile integrated module as claimed in claim 10 where, in the steps of providing the plurality of first sheets and providing the plurality of second sheets, the pluralities provided result in the common via extending in a range from
25 approximately 75 μm to approximately one half of a distance between a lower surface of a lower sheet and an upper surface of an upper sheet.

12. A method of fabricating a low profile integrated module as claimed in claim 1 wherein the step of forming the via includes forming a hole with a cross-sectional dimension in a range of approximately 125 μm to
5 approximately 500 μm .

13. A method of fabricating a low profile integrated module as claimed in claim 12 wherein the step of forming the hole further includes forming a plurality of adjacent,
10 partially overlapping, holes to define a single via with an elongated cross-section.

14. A method of fabricating a low profile integrated module as claimed in claim 1 further including a step of
15 providing a connection pad on a surface of each module and contacting the portion of the via filled with conductive metal in the periphery.

15. A method of fabricating a low profile integrated
20 module as claimed in claim 14 wherein the step of providing the connection pad includes providing a connection pad with a contact surface area substantially greater than a cross-sectional area of the portion of the via.

25

16. A method of fabricating a low profile integrated
module as claimed in claim 1 wherein the step of forming
the via includes forming a plurality of spaced apart vias
5 and further including a step of providing a stress relief
anchor pad spaced approximately an equal distance from
each of the plurality of spaced apart vias.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22

17. A method of fabricating a low profile integrated module comprising the steps of:

providing a plurality of first sheets of unfired ceramic material each defining two adjacent integrated module first components, and forming a plurality of vias extending through the plurality of first sheets between the two adjacent integrated module first components;

filling each of the plurality of vias with a conductive metal paste;

10 providing a plurality of second sheets of unfired ceramic material each defining two adjacent integrated module second components;

fixing the plurality of first sheets and the plurality of second sheets in overlying relationship with the two adjacent integrated module first components aligned with the two adjacent integrated module second components to form two adjacent integrated modules;

cutting the fixed pluralities of first and second sheets, through the pluralities of vias to separate the fixed pluralities of first and second sheets into two separate integrated modules, each module having a portion of each of the plurality of vias in a periphery thereof and extending along a portion of the periphery; and

firing the two separate integrated modules at a firing temperature high enough to form ceramic modules, the conductive metal having a melting temperature greater than the firing temperature.

18. A method of fabricating a low profile integrated module as claimed in claim 17 wherein the step of providing the plurality of first sheets of unfired ceramic material further includes providing one of the plurality
5 of first sheets of unfired ceramic material with an enlarged opening in communication with one of the plurality of vias.

19. A method of fabricating a low profile integrated
10 module as claimed in claim 17 wherein the step of providing one of the plurality of first sheets of unfired ceramic material with an enlarged opening includes a step of at least partially filling the enlarged opening with the conductive metal paste.

15

20. A method of fabricating a low profile integrated module as claimed in claim 17 wherein the step of fixing the pluralities of first and second sheets of unfired ceramic material in overlying relationship aligns vias in
20 the plurality of first sheets of unfired ceramic material to produce a common via extending partially through the two adjacent integrated modules from a lower surface of a lower sheet of unfired ceramic material to an upper surface of an intermediate sheet of unfired ceramic
25 material.

21. A method of fabricating a low profile integrated module as claimed in claim 20 where, in the steps of providing the plurality of first sheets of unfired ceramic material and providing the plurality of second sheets of unfired ceramic material, the pluralities provided result in the common via extending in a range from approximately 25 μm to approximately one half of a distance between a lower surface of a lower sheet of unfired ceramic material and an upper surface of an upper sheet of unfired ceramic material.

22. A method of fabricating a low profile integrated module as claimed in claim 17 wherein the step of forming the via includes forming a hole with a cross-sectional dimension in a range of approximately 125 μm to approximately 500 μm .

23. A method of fabricating a low profile integrated module as claimed in claim 22 wherein the step of forming the hole further includes forming a plurality of adjacent, partially overlapping holes to define a single via with an elongated cross-section.

24. A method of fabricating a low profile integrated module as claimed in claim 17 further including a step of providing a stress relief anchor pad on an exposed surface of one of the plurality of first sheets of unfired ceramic material, the stress relief anchor pad being spaced approximately an equal distance from each of the plurality of spaced apart vias.

25. A method of fabricating a low profile integrated module comprising the steps of:

providing a first sheet of material defining two adjacent integrated module first components, and forming a plurality of spaced apart vias extending through the first sheet between the two adjacent integrated module first

components;

providing two stress relief anchor pads on a surface of the first sheet of material, one each of the two stress relief anchor pads being positioned within each of the two adjacent integrated module first components, and each of the two stress relief anchor pads being spaced approximately an equal distance from each of the plurality of vias;

filling the plurality of vias with a conductive metal;

providing a second sheet of material defining two adjacent integrated module second components;

fixing the first and second sheets in overlying relationship with the two adjacent integrated module first

components aligned with the two adjacent integrated module
second components to form two adjacent integrated modules,
the second sheet of material being fixed to a surface of
the first sheet of material opposite the surface of the
5 first sheet of material having the two stress relief
anchor pads thereon; and

cutting the first and second sheets, through the via
to separate the first and second sheets into separate
integrated modules, each module having one of the two
10 stress relief anchor pads and a portion of each of the
plurality of vias in a periphery thereof.

26. A method of connecting a low profile integrated module to a supporting substrate comprising the steps of:

providing a low profile integrated module including a plurality of sheets of material fixed together to form the module and defining a lower module surface, an upper module surface, and side module surfaces, the module further including a via extending through at least one of the plurality of sheets from the lower module surface partially to the upper module surface and in a side module surface, the via being filled with a conductive material;

providing a supporting substrate having a mounting pad on a mounting surface thereof, the mounting pad having an upper surface greater in area than a lower surface of the via;

positioning the lower module surface adjacent the upper surface of the mounting pad; and

soldering the via to the mounting pad so that solder wicks up the via along the side module surface.

27. A method of connecting a low profile integrated module to a supporting substrate as claimed in claim 26 wherein the steps of providing the supporting substrate having the solder pad and soldering the via include providing a standoff height between the module and the supporting substrate in a range of approximately 25 μm to 500 μm .

28. A low profile integrated module comprising:

a plurality of first integrated module components
affixed together in overlying relationship with a
plurality of common vias extending therethrough from a
lower to an upper surface and positioned in side surfaces;

a plurality of second integrated module components
fixed together in overlying relationship, the plurality of
first components and the plurality of second components
being affixed together and aligned to form an integrated
module with the plurality of vias extending from a lower
surface of the module toward an upper surface of the
module partially along at least one side surface of the
module; and

the plurality of vias being filled with conductive
material.

29. A low profile integrated module as claimed in
claim 28 wherein each via of the plurality of vias extends
from the lower surface of the module partially along the
at least one side surface of the module a distance in a
range of approximately 75 μm to approximately one half of
the distance between the lower surface of the module and
the upper surface of the module.

30. A low profile integrated module mounted on a supporting substrate, the assembly comprising:

a module including a plurality of first integrated module components affixed together in overlying

5 relationship with a plurality of common vias extending therethrough from a lower to an upper surface and positioned in side surfaces, and a plurality of second integrated module components fixed together in overlying relationship, the plurality of first components and the
10 plurality of second components being affixed together and aligned to form an integrated module with the plurality of vias extending from a lower surface of the module toward an upper surface of the module partially along at least one side surface of the module;

15 a supporting substrate having an upper surface with a plurality of connecting pads formed on the upper surface, the lower surface of the module positioned adjacent the upper surface of the supporting substrate with each via of the plurality of vias overlying an associated different
20 one of the plurality of connecting pads; and

solder connecting each via of the plurality of vias to the associated connecting pad, the solder extending from the associated connecting pad at least partially along the via to form a fillet between each of the vias
25 and the associated connecting pad.

31. An assembly as claimed in claim 30 wherein the lower surface of the module and the upper surface of the supporting substrate are separated by a standoff height in
5 a range of approximately 25 μm to approximately 125 μm .

32. An assembly as claimed in claim 30 wherein each via of the plurality of vias extends from the lower surface of the module partially along the at least one
10 side surface of the module a distance in a range of approximately 75 μm to approximately one half of the distance between the lower surface of the module and the upper surface of the module.

LOW PROFILE INTEGRATED MODULE INTERCONNECTS
AND METHOD OF FABRICATION


Abstract of the Disclosure

10


15

20


A low profile integrated module is fabricated to include sheets of material, such as ceramic or PCB, fixed together and including a via extending through at least one of the plurality of sheets from the lower module surface partially to the upper module surface and in a side module surface. The via is filled with conductive material. The module is then mounted on a supporting substrate having a solder pad on the mounting surface with an area greater than the lower surface of the via. The lower surface of the via is positioned adjacent the upper surface of the mounting pad and soldered so that solder wicks up the via along the side module surface.



- PRIOR ART -

FIG. 1**FIG. 2**

- PRIOR ART -

**FIG. 3**




FIG. 4

25






FIG. 5

21

**FIG. 6****FIG. 7**




FIG. 8




FIG. 9




FIG. 10




FIG. 11

**COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION**

Attorney Docket CT00-020

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below), or an original, first and joint inventor (if plural names are listed below), of the subject matter which is claimed and for which a patent is sought on the invention entitled LOW PROFILE INTEGRATED MODULE INTERCONNECTS AND METHOD OF FABRICATION, the specification of which is attached hereto unless the following box is checked:

☐ Application was filed on _____
as Application No. _____
and was amended on _____.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) or 365(b) any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)		Priority Claimed
(Number) _____	(Country) _____	(Day/Month/Year Filed) <input type="checkbox"/> Yes <input type="checkbox"/> No
(Number) _____	(Country) _____	(Day/Month/Year Filed) <input type="checkbox"/> Yes <input type="checkbox"/> No

I hereby claim the benefit under Title 35, United States Code, § 119 of any United States provisional application(s), listed below:

(Application Number) _____	(Filing Date) _____
(Application Number) _____	(Filing Date) _____

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below:

(U.S. Parent Application Number or PCT Parent No.) _____	(Filing Date) _____	(Country) _____
(U.S. Parent Application Number or PCT Parent No.) _____	(Filing Date) _____	(Country) _____

I hereby appoint the attorney(s) and/or agent(s) associated with Customer Number 23330 to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.

Address all telephone calls to Mr. William E. Koch at telephone no. (480) 441-4281.

Address all correspondence to customer number 23330.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF FIRST INVENTOR: FIRST MIDDLE LAST		INVENTOR'S SIGNATURE	DATE (SPELL OUT MONTH)
Chia-Yu Fu		<i>Chia-Yu Fu</i>	11 / 14 / 00
RESIDENCE:		CITIZENSHIP:	
3200 W. Frankfurt Drive, Chandler, AZ 85226		Taiwan	
POST OFFICE ADDRESS:			
Same as above			

FULL NAME OF SECOND INVENTOR: FIRST MIDDLE LAST			INVENTOR'S SIGNATURE		DATE: (SPELLOUT MONTH)
Thomas A. Wetteroth					
RESIDENCE: 1061 N. Ash Drive, Chandler, AZ 85224				CITIZENSHIP: United States	
POST OFFICE ADDRESS: Same as above					

FULL NAME OF THIRD INVENTOR: FIRST MIDDLE LAST			INVENTOR'S SIGNATURE		DATE (SPELL OUT MONTH)	
Rong-Fong Huang						
RESIDENCE: 1969 E. Palomino Drive, Tempe, AZ 85284					CITIZENSHIP: United States	
POST OFFICE ADDRESS: Same as above						